

## KreteSuperPlast 700

KreteSuperPlast 700 is a high performance admixture designed to offer superior plasticizing action, mid to high range water reduction, and densification in precast and self-consolidating concrete products.

### FEATURES

- Plasticizing Action
- Mid to High Range Water Reduction (25-40% Reduction)
- Densification
- Polycarboxylate Chemistries

### BENEFITS

- Improves Batch Consistency
- Improves Green Strength
- Improves Surface Texture
- Allows Proper Spread Without Segregation
- Little to No Vibration Needed
- Provides Sharp Corners and Edges

### TECHNICAL INFORMATION

<u>Parameter</u>	<u>Typical Value</u>
Appearance	Hazy Amber Liquid
Specific Gravity	1.078
Lbs./Gal	8.99
pH	5.08
IR	Pass

### DIRECTIONS FOR USE

1. Use 1/3 less water per batch when using KreteSuperPlast 700.
2. Use at dosage rate of 3 - 16 fluid ounces per 100 lbs. cementitious material.
3. Add after introduction of pre-wet aggregates.
4. Check air content.

*Note: Dosage rate will vary depending on mix design.*

*Note: For self-consolidating concrete, higher dosage rates are required (14 - 16 fluid ounces per 100 lbs. cementitious material).*

### PRODUCT PACKAGING

Available in 330 US gallon totes, 55 US gallon drums, and 5 US gallon pails. Samples are available by request.

### PRODUCT STORAGE AND SHELF LIFE

Store in dry area. Keep containers tightly closed. Do not store in excessively high temperatures (>100 F°). KEEP FROM FREEZING.

Avoid physical damage to containers.

KreteSuperPlast 700 has a rheological shelf life of eight (8) months in original, unopened packaging.

*The information presented above is true and accurate to the best of our knowledge. No warranty or guarantee, expressed or implied is made regarding the performance of the product. This information is not intended to be all-inclusive concerning handling, storage and use of the product. Health and other regulatory factors are the responsibility of the customer.*

For Industrial Use Only.  
Not for internal consumption.  
Consult SDS for safety and regulatory information.

PDS - SuperPlast 700 - 01/2016