

## KreteRelease 490

(Formerly Krete Pallet Lease)

KreteRelease 490 is an aqueous, corrosion inhibitive coating and release agent designed to prevent sticking of concrete masonry units to steel pallets and to protect steel pallets and molds.

### FEATURES

- Water Based
- Corrosion Inhibitive Coating

### BENEFITS

- Environmentally Friendly
- Negligible VOC's
- Prevents Sticking of Masonry to Pallets
- Increases Service Life of Pallets
- Increases Service Life of Molds
- Effective for Long-Term Pallet Storage
- Effective for Long-Term Mold Storage

### TECHNICAL INFORMATION

<u>Parameter</u>	<u>Typical Value</u>
Appearance	Opaque Tan Liquid
Specific Gravity	0.994
Lbs./Gal	8.29
pH	8.00
IR	Pass

### DIRECTIONS FOR USE

1. No dilution or mixing is required prior to application.
2. Apply a thin, even coating to pallets or molds by sprayer or roller system.
3. Avoid over application to prevent runs or puddles, which will create voids in the finished concrete surface.

*Note: After numerous applications at full strength, it may be possible to apply subsequent diluted applications for greater economies. The dilution factor employed will be dependent on desired efficacy and economies.*

*Test at 1:1, 1:2, and 1:3 parts water to determine suitable strength.*

### PRODUCT PACKAGING

Available in 330 US gallon totes, 55 US gallon drums, and 5 US gallon pails. Samples are available by request.

### PRODUCT STORAGE AND SHELF LIFE

Store in dry area. Keep containers tightly closed. Do not store in excessively high temperatures (>100 F°). KEEP FROM FREEZING.

Avoid physical damage to containers.

KreteRelease 490 has a rheological shelf life of eight (8) months in original, unopened packaging.

*The information presented above is true and accurate to the best of our knowledge. No warranty or guarantee, expressed or implied is made regarding the performance of the product. This information is not intended to be all-inclusive concerning handling, storage and use of the product. Health and other regulatory factors are the responsibility of the customer.*

For Industrial Use Only.  
Not for internal consumption.  
Consult SDS for safety and regulatory information.

PDS - Release 490 - 01/2016