

KreteXcel 510

(Formerly Krete XL-25)

KreteXcel 510 is a highly concentrated, non-chloride cement hydration accelerator designed to offer effective plasticizing action in zero-slump concrete products.

FEATURES

- Highly Concentrated
- Accelerates Concrete Curing
- Plasticizing Action
- Non-Chloride

BENEFITS

- Reduces Curing Costs
- Non-Corrosive
- Provides High Early Strength
- Improves Cold Water Curing
- Improves Batch Consistency
- Decreases Machine Feed Time
- Improves Finish Texture
- Improves Cold Weather Curing

TECHNICAL INFORMATION

<u>Parameter</u>	<u>Typical Value</u>
Appearance	Light Green Liquid
Specific Gravity	1.138
Lbs./Gal	9.49
pH	10.58
IR	Pass

DIRECTIONS FOR USE

1. Use at dosage rate of 1.5 - 4 fluid ounces per 100 lbs. of cementitious material.
2. Add with the final batch water.
3. For Ribbon Mixers: Mix for 60 seconds after addition of admixture.
For Pan Mixers: Mix for 30 seconds after addition of admixture.

PRODUCT PACKAGING

Available in 330 US gallon totes, 55 US gallon drums, and 5 US gallon pails. Samples are available by request.

PRODUCT STORAGE AND SHELF LIFE

Store in dry area. Keep containers tightly closed. Do not store in excessively high temperatures (>100 F°). KEEP FROM FREEZING. Avoid physical damage to containers. KreteXcel 510 has a rheological shelf life of eight (8) months in original, unopened packaging.

The information presented above is true and accurate to the best of our knowledge. No warranty or guarantee, expressed or implied is made regarding the performance of the product. This information is not intended to be all-inclusive concerning handling, storage and use of the product. Health and other regulatory factors are the responsibility of the customer.

For Industrial Use Only.
Not for internal consumption.
Consult SDS for safety and regulatory information.

PDS - Xcel 510 - 01/2016

KreteXcel 510

(Formerly Krete XL-25)

KreteXcel 510 is a highly concentrated, non-chloride cement hydration accelerator for precast concrete products.

FEATURES

- Highly Concentrated
- Accelerates Concrete Curing
- Non-Chloride

BENEFITS

- Reduces Curing Costs
- Non-Corrosive
- Provides High Early Strength
- Improves Cold Water Curing
- Improves Cold Weather Curing

TECHNICAL INFORMATION

<u>Parameter</u>	<u>Typical Value</u>
Appearance	Light Green Liquid
Specific Gravity	1.138
Lbs./Gal	9.49
pH	10.58
IR	Pass

DIRECTIONS FOR USE

1. Use at dosage rate of 4 - 16 fluid ounces per 100 lbs. of cementitious material
2. Add with the final batch water.
3. For Ribbon Mixers: Mix for 60 seconds after addition of admixture.
For Pan Mixers: Mix for 30 seconds after addition of admixture.

PRODUCT PACKAGING

Available in 330 US gallon totes, 55 US gallon drums, and 5 US gallon pails. Samples are available by request.

PRODUCT STORAGE AND SHELF LIFE

Store in dry area. Keep containers tightly closed. Do not store in excessively high temperatures (>100 F°). KEEP FROM FREEZING. Avoid physical damage to containers. KreteXcel 510 has a rheological shelf life of eight (8) months in original, unopened packaging.

The information presented above is true and accurate to the best of our knowledge. No warranty or guarantee, expressed or implied is made regarding the performance of the product. This information is not intended to be all-inclusive concerning handling, storage and use of the product. Health and other regulatory factors are the responsibility of the customer.

For Industrial Use Only.
Not for internal consumption.
Consult SDS for safety and regulatory information.

PDS - Xcel 510 - 01/2016