

KreteSelect 920

(Formerly Krete Retarder)

KreteSelect 920 is an admixture designed to offer retarding action in the initial and final set of Portland cement while offering plasticizing action in zero-slump and precast concrete.

FEATURES

- Retards Initial and Final Set of Cement
- Plasticizing Action
- Non-Chloride

BENEFITS

- Increases Finish Time
- Improves Batch Consistency
- Decreases Machine Feed Time
- Improves Green Strength
- Non-Corrosive

TECHNICAL INFORMATION

<u>Parameter</u>	<u>Typical Value</u>
Appearance	Clear Yellow to Amber Liquid
Specific Gravity	1.161
Lbs./Gal	9.68
pH	10.21
IR	Pass

DIRECTIONS FOR USE

1. Add after the final batch water at the dosage rate displayed by the table below.

Note: Use of KreteSelect 920 may reduce amount of water required for desired slump.

APPLICATION RATES

<u>Air or Concrete Temperature</u>	<u>Dosage per 100 lbs. of Cementitious Material</u>
40 - 70 °F	2 fluid ounces
71 - 80 °F	3 fluid ounces
81 - 90 °F	4 fluid ounces
91 °F or above	5 fluid ounces

PRODUCT PACKAGING

Available in 330 US gallon totes, 55 US gallon drums, and 5 US gallon pails. Samples are available by request.

PRODUCT STORAGE AND SHELF LIFE

Store in dry area. Keep containers tightly closed. Do not store in excessively high temperatures (>100 F°). KEEP FROM FREEZING.

Avoid physical damage to containers.

KreteSelect 920 has a rheological shelf life of eight (8) months in original, unopened packaging.

The information presented above is true and accurate to the best of our knowledge. No warranty or guarantee, expressed or implied is made regarding the performance of the product. This information is not intended to be all-inclusive concerning handling, storage and use of the product. Health and other regulatory factors are the responsibility of the customer.

For Industrial Use Only.
Not for internal consumption.
Consult SDS for safety and regulatory information.

PDS - Select 920 - 01/2016