

KreteControl 230

(Formerly KreteControl 300)

KreteControl 230 is a non-aqueous, reactive admixture designed to offer integral water repellency and both primary and secondary efflorescence control in precast concrete products at low dosage rates.

FEATURES

- Water Repellency
- Efflorescence Control

BENEFITS

- Minimizes Water Penetration/Absorption
- Improves Service Life of Units
- Improves Aesthetic Appearance of Units
- Promotes and Maintains Brighter Colors

TECHNICAL INFORMATION

<u>Parameter</u>	<u>Typical Value</u>
Appearance	Clear Liquid
Specific Gravity	0.893
Lbs./Gal	7.44
IR	Pass

DIRECTIONS FOR USE

1. For Efflorescence Control: Use at dosage rate of 2 - 4 fluid ounces per 100 lbs. of cementitious material.
2. Add after the introduction of the pre-wet aggregates.
3. Mix for 90 seconds after addition of admixture.
4. Check the moisture content of the mix and add additional water if needed.

PRODUCT PACKAGING

Available in 330 US gallon totes, 55 US gallon drums, and 5 US gallon pails. Samples are available by request.

PRODUCT STORAGE AND SHELF LIFE

Store in dry area. Keep containers tightly closed. Do not store in excessively high temperatures (>100 F°). KEEP FROM FREEZING. Avoid physical damage to containers. KreteControl 230 has a rheological shelf life of eight (8) months in original, unopened packaging.

The information presented above is true and accurate to the best of our knowledge. No warranty or guarantee, expressed or implied is made regarding the performance of the product. This information is not intended to be all-inclusive concerning handling, storage and use of the product. Health and other regulatory factors are the responsibility of the customer.

For Industrial Use Only.
Not for internal consumption.
Consult SDS for safety and regulatory information.

PDS - Control 230 - 01/2016