

KreteMix 121 (Formerly Krete Plast II)

KreteMix 121 is an aqueous, moderate swipe producing admixture designed to offer plasticizing action in zero- slump concrete products.

FEATURES

- Plasticizing Action
- Highly Concentrated

BENEFITS

- Improves Batch Consistency
- Decreases Machine Feed Time
- Low Dosage vs. Traditional Admixtures
- Produces Moderate Swipe

TECHNICAL INFORMATION

<u>Parameter</u>	<u>Typical Value</u>
Appearance	Clear Pale Yellow Liquid
Specific Gravity	1.042
Lbs./Gal	8.69
pH	8.38
IR	Pass

DIRECTIONS FOR USE

1. Concrete Block, Pavers, or Roof Tile: Use at dosage rate of 0.5 fluid ounces per 100 lbs. of cementitious material.
Concrete Pipe: Use at dosage rate of 1 - 1.5 fluid ounces per 100 lbs. of cementitious material.
2. Add after the main portion of batch water.
3. Mix for 60 seconds after addition of admixture.

Note: For high volume output dispensers, KreteMix 121 may be diluted up to 10 parts water before addition to batching equipment.

PRODUCT PACKAGING

Available in 330 US gallon totes, 55 US gallon drums, and 5 US gallon pails. Samples are available by request.

PRODUCT STORAGE AND SHELF LIFE

Store in dry area. Keep containers tightly closed. Do not store in excessively high temperatures (>100 F°). KEEP FROM FREEZING. Avoid physical damage to containers. KreteMix 121 has a rheological shelf life of eight (8) months in original, unopened packaging.

The information presented above is true and accurate to the best of our knowledge. No warranty or guarantee, expressed or implied is made regarding the performance of the product. This information is not intended to be all-inclusive concerning handling, storage and use of the product. Health and other regulatory factors are the responsibility of the customer.

For Industrial Use Only.
Not for internal consumption.
Consult SDS for safety and regulatory information.

PDS - Mix 121 - 01/2016