

KreteRelease 440

(Formerly Krete Coat)

KreteRelease 440 is a high performance release agent designed to offer superior mixer and form release properties in specialty and white concrete precast products.

FEATURES

- Heavy Naphthenic Based
- High Performance Chemistry

BENEFITS

- Economical
- Fuel and Diesel Oil Free
- Provides Smoother Surfaces
- Forms Long Lasting Film
- Can Dilute with Oil or Solvent
- Non-Staining

TECHNICAL INFORMATION

<u>Parameter</u>	<u>Typical Value</u>
Appearance	Light Amber Oily Liquid
Specific Gravity	0.891
Lbs./Gal	7.43
IR	Pass

DIRECTIONS FOR USE

For Mixers:

1. Use at full strength or dilute with heavy naphthenic oil.
2. Spray apply.

For Tough Forms:

1. Dilute with 1 - 3 parts mineral spirits, kerosene, or diesel fuel.
2. Spray apply.
3. Wipe out any excess from form corners.

PRODUCT PACKAGING

Available in 55 US gallon drums and 5 US gallon pails.
Samples are available by request.

PRODUCT STORAGE AND SHELF LIFE

Store in dry area. Keep containers tightly closed. Do not store in excessively high temperatures (>100 F°). KEEP FROM FREEZING.
Avoid physical damage to containers.
KreteRelease 440 has a rheological shelf life of eight (8) months in original, unopened packaging.

The information presented above is true and accurate to the best of our knowledge. No warranty or guarantee, expressed or implied is made regarding the performance of the product. This information is not intended to be all-inclusive concerning handling, storage and use of the product. Health and other regulatory factors are the responsibility of the customer.

For Industrial Use Only.
Not for internal consumption.
Consult SDS for safety and regulatory information.

PDS - Release 440 - 01/2016