

## KreteMix 105 (Formerly Krete Maxi-Slump)

KreteMix 105 is an aqueous admixture designed to offer plasticizing action while allowing increased water use in slump block products.

### FEATURES

- Plasticizing Action
- Allows Increased Water Use

### BENEFITS

- Improves Batch Consistency
- Decreases Machine Feed Time
- Improves Green Strength
- Improves Finish Texture
- Effectively Hydrates Cement
- Improves Compressive Strength

### TECHNICAL INFORMATION

<u>Parameter</u>	<u>Typical Value</u>
Appearance	Dark Brown Liquid
Specific Gravity	1.024
Lbs./Gal	8.54
pH	11.44
IR	Pass

### DIRECTIONS FOR USE

1. Use at dosage rate of 2 fluid ounces per 100 lbs. of cementitious material.
2. Add after the main portion of batch water.

### PRODUCT PACKAGING

Available in 330 US gallon totes, 55 US gallon drums, and 5 US gallon pails. Samples are available by request.

### PRODUCT STORAGE AND SHELF LIFE

Store in dry area. Keep containers tightly closed. Do not store in excessively high temperatures (>100 F°). **KEEP FROM FREEZING.**

Avoid physical damage to containers.

KreteMix 105 has a rheological shelf life of eight (8) months in original, unopened packaging.

*The information presented above is true and accurate to the best of our knowledge. No warranty or guarantee, expressed or implied is made regarding the performance of the product. This information is not intended to be all-inclusive concerning handling, storage and use of the product. Health and other regulatory factors are the responsibility of the customer.*

For Industrial Use Only.  
Not for internal consumption.  
Consult SDS for safety and regulatory information.

PDS - Mix 105 - 01/2016