

## KreteSelect 930

(Formerly Krete Modifier)

KreteSelect 930 is an admixture designed to offer plasticizing action and improved flexural strength in zero-slump and precast concrete products.

### FEATURES

- Plasticizing Action
- Improved Flexural Strength

### BENEFITS

- Improves Workability
- Improves Green Strength
- Improves Surface Texture
- Improves Service Life of Concrete Products

### TECHNICAL INFORMATION

<u>Parameter</u>	<u>Typical Value</u>
Appearance	Milky White Liquid
Specific Gravity	1.025
Lbs./Gal	8.54
pH	9.80
IR	Pass

### DIRECTIONS FOR USE

1. Use at dosage rate of 0.5 - 2 US gallons per 100 lbs. of cementitious material.
2. After addition, add small amounts of water to mix if necessary.

### PRODUCT PACKAGING

Available in 330 US gallon totes, 55 US gallon drums, and 5 US gallon pails. Samples are available by request.

### PRODUCT STORAGE AND SHELF LIFE

Store in dry area. Keep containers tightly closed. Do not store in excessively high temperatures (>100 F°). KEEP FROM FREEZING.

Avoid physical damage to containers.

KreteSelect 930 has a rheological shelf life of eight (8) months in original, unopened packaging.

*The information presented above is true and accurate to the best of our knowledge. No warranty or guarantee, expressed or implied is made regarding the performance of the product. This information is not intended to be all-inclusive concerning handling, storage and use of the product. Health and other regulatory factors are the responsibility of the customer.*

For Industrial Use Only.  
Not for internal consumption.  
Consult SDS for safety and regulatory information.

PDS - Select 930 - 01/2016