

KreteSelect 910

(Formerly Krete DF - Defoamer)

KreteSelect 910 is an aqueous solution designed to reduce macro foam created in the mixing process of zero-slump and precast concrete products.

FEATURES

- Easy to Use Liquid
- Reduces Macro Foam in Mixing
- Versatile Formula

BENEFITS

- Effective with Most Mix Designs
- Improves Compression Strength
- Decreases Water Permeability

TECHNICAL INFORMATION

<u>Parameter</u>	<u>Typical Value</u>
Appearance	Translucent Blue to Gray Liquid
Specific Gravity	0.998
Lbs./Gal	8.33
pH	9.80
IR	Pass

DIRECTIONS FOR USE

1. Use at dosage rate of 1 - 2 fluid ounces per 100 lbs. of cementitious material.
2. Add with the final batch water.
3. Mix for 60 seconds after the addition of the admixture or until foam dissipates.

Note: If foam persists, add additional KreteSelect 910 and repeat steps.

PRODUCT PACKAGING

Available in 55 US gallon drums, and 5 US gallon pails.
Samples are available by request.

PRODUCT STORAGE AND SHELF LIFE

Store in dry area. Keep containers tightly closed. Do not store in excessively high temperatures (>100 F°). KEEP FROM FREEZING.
Avoid physical damage to containers.
KreteSelect 910 has a rheological shelf life of eight (8) months in original, unopened packaging.

The information presented above is true and accurate to the best of our knowledge. No warranty or guarantee, expressed or implied is made regarding the performance of the product. This information is not intended to be all-inclusive concerning handling, storage and use of the product. Health and other regulatory factors are the responsibility of the customer.

For Industrial Use Only.
Not for internal consumption.
Consult SDS for safety and regulatory information.

PDS - Select 910 - 01/2016