

KreteSeal 650

(Formerly Krete Highliter™ 2)

KreteSeal 650 is a penetrating sealer designed to enhance the natural color of aggregates and integral pigments in zero-slump concrete products.

FEATURES

- Water Based
- Penetrating Chemistry

BENEFITS

- Promotes and Maintains Brighter Colors
- Non-Yellowing
- UV Resistant
- Breathable Coating
- Reduces Water Penetration

TECHNICAL INFORMATION

| <u>Parameter</u> | <u>Typical Value</u> |
|------------------|--------------------------------------|
| Appearance | Hazy Colorless to Pale Yellow Liquid |
| Specific Gravity | 1.009 |
| Lbs./Gal | 8.41 |
| pH | 10.34 |
| IR | Pass |

DIRECTIONS FOR USE

It is recommended that KreteSeal 650 be applied to a small test area prior to full or final application.

KreteSeal 650 should be applied in temperatures exceeding 50° F.

1. Apply by spray or deep nap roller.
2. For increased durability, top coat with a suitable finish sealer (breathable urethane or acrylic based).

PRODUCT PACKAGING

Available in 55 US gallon drums and 5 US gallon pails. Samples are available by request.

PRODUCT STORAGE AND SHELF LIFE

Store in dry area. Keep containers tightly closed. Do not store in excessively high temperatures (>100 F°). **KEEP FROM FREEZING.**

Avoid physical damage to containers.

KreteSeal 650 has a rheological shelf life of eight (8) months in original, un-opened packaging.

The information presented above is true and accurate to the best of our knowledge. No warranty or guarantee, expressed or implied is made regarding the performance of the product. This information is not intended to be all-inclusive concerning handling, storage and use of the product. Health and other regulatory factors are the responsibility of the customer.

For Industrial Use Only.
Not for internal consumption.
Consult SDS for safety and regulatory information.

PDS - Seal 650 - 01/2016