

KreteRelease 410

(Formerly Krete Release Agent)

KreteRelease 410 is a low viscosity, high performance release agent designed to offer superior mold release in precast applications.

FEATURES

- Low Viscosity
- High-Performance Chemistry
- VOC Compliant

BENEFITS

- Economical
- Sprays Easily
- Forms Long-Lasting Resistant Film
- Provides Smoother Cast Surfaces
- Meets 1998 Federal VOC Requirements

TECHNICAL INFORMATION

<u>Parameter</u>	<u>Typical Value</u>
Appearance	Light Amber Liquid
Specific Gravity	0.860
Lbs./Gal	7.17
IR	Pass

DIRECTIONS FOR USE

1. Form surfaces should be dry and free of concrete build-up prior to application.
2. No dilution or mixing is required prior to application (Can dilute 1:1 with a suitable diluent such as mineral spirits, kerosene, or diesel fuel).
3. Spray apply a thin uniform coating.
4. Avoid over application to prevent runs or puddles, which will create voids in the finished concrete surface.

PRODUCT PACKAGING

Available in 330 US gallon totes, 55 US gallon drums, and 5 US gallon pails. Samples are available by request.

PRODUCT STORAGE AND SHELF LIFE

Store in dry area. Keep containers tightly closed. Do not store in excessively high temperatures (>100 F°). KEEP FROM FREEZING. Avoid physical damage to containers. KreteRelease 410 has a rheological shelf life of eight (8) months in original, unopened packaging.

The information presented above is true and accurate to the best of our knowledge. No warranty or guarantee, expressed or implied is made regarding the performance of the product. This information is not intended to be all-inclusive concerning handling, storage and use of the product. Health and other regulatory factors are the responsibility of the customer.

For Industrial Use Only.
Not for internal consumption.
Consult SDS for safety and regulatory information.

PDS - Release 410 - 01/2016