

KreteSelect 950

(Formerly Krete Rack Coat)

KreteSelect 950 is a gelatinous coating designed to offer corrosion inhibitive protection on racks in block plants.

FEATURES

- Stabilized Formulation
- Corrosion Inhibitive Protection
- VOC Compliant

BENEFITS

- No Sagging Up to 220 °F
- Lasts for Up to 2 Years
- Meets 1998 Federal VOC Requirements
- Durable in Steam/Mist Kilns

TECHNICAL INFORMATION

<u>Parameter</u>	<u>Typical Value</u>
Appearance	Dark Amber Gel
Specific Gravity	0.900
Lbs./Gal	7.51
IR	Pass

DIRECTIONS FOR USE

1. Remove any loose rust from racks with wire brush.
2. Estimate approximately 1 US Gallon for every 100 block (depending on rack size).
3. Apply even coating approximately 1/16 - 1/8 inch thick on all exposed metal rack surfaces.
4. Reapply to high contact areas as necessary.

Note: Car wash mitts work well for application.

PRODUCT PACKAGING

Available in 35 lbs. plastic pails.

PRODUCT STORAGE AND SHELF LIFE

Store in dry area. Keep containers tightly closed. Do not store in excessively high temperatures (>100 F°). KEEP FROM FREEZING. Avoid physical damage to containers. KreteSelect 950 has a rheological shelf life of eight (8) months in original, unopened packaging.

The information presented above is true and accurate to the best of our knowledge. No warranty or guarantee, expressed or implied is made regarding the performance of the product. This information is not intended to be all-inclusive concerning handling, storage and use of the product. Health and other regulatory factors are the responsibility of the customer.

For Industrial Use Only.
Not for internal consumption.
Consult SDS for safety and regulatory information.

PDS - Select 950 - 01/2016