

KreteMix 150 (Formerly Krete Ultra Mix)

KreteMix 150 is an aqueous, moderate swipe producing admixture designed to offer plasticizing action and increased water use in zero-slump concrete products.

FEATURES

- Plasticizing Action
- Allows Increased Water Use

BENEFITS

- Improves Batch Consistency
- Decreases Machine Feed Time
- Improves Green Strength
- Improves Finish Texture
- Effectively Hydrates Cement
- Improves Compressive Strength
- Provides Moderate Swipe

TECHNICAL INFORMATION

<u>Parameter</u>	<u>Typical Value</u>
Appearance	Clear Green Liquid
Specific Gravity	1.032
Lbs./Gal	8.61
pH	10.47
IR	Pass

DIRECTIONS FOR USE

1. Use at dosage rate of 1 - 1.5 fluid ounces per 100 lbs. of cementitious material.
2. Add with the main portion of batch water.

PRODUCT PACKAGING

Available in 330 US gallon totes, 55 US gallon drums, and 5 US gallon pails. Samples are available by request.

PRODUCT STORAGE AND SHELF LIFE

Store in dry area. Keep containers tightly closed. Do not store in excessively high temperatures (>100 F°). KEEP FROM FREEZING. Avoid physical damage to containers. KreteMix 150 has a rheological shelf life of eight (8) months in original, unopened packaging.

The information presented above is true and accurate to the best of our knowledge. No warranty or guarantee, expressed or implied is made regarding the performance of the product. This information is not intended to be all-inclusive concerning handling, storage and use of the product. Health and other regulatory factors are the responsibility of the customer.

For Industrial Use Only.
Not for internal consumption.
Consult SDS for safety and regulatory information.

PDS - Mix 150 - 01/2017